

Proxima C5 Compact (Ultralight SV1) Projector

Technical and Functional Specifications

Display Technology	<ul style="list-style-type: none">• 0.9 in. polysilicon LCD x 3
Resolution	<ul style="list-style-type: none">• SVGA (800 X 600)
Resolution Supported	<ul style="list-style-type: none">• VGA (640 x 480) XGA (1024 x 768)
Number of Colors	<ul style="list-style-type: none">• 16.7 million colors
Brightness	<ul style="list-style-type: none">• 700 ANSI lumens
Contrast Ratio	<ul style="list-style-type: none">• 300:1 (full-on, full-off)
Computer Compatibility	<ul style="list-style-type: none">• IBM PC or compatibles• Apple Macintosh• Workstations up to 140 MHz
Video Compatibility	<ul style="list-style-type: none">• NTSC 3.58, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, MESECAM
Input Sources	<ul style="list-style-type: none">• 1 computer, 1 video, 1 S-video, 2 audio
H-Sync Range	<ul style="list-style-type: none">• 15-100 kHz
V-Sync Range	<ul style="list-style-type: none">• 43-130 Hz
Bandwidth	<ul style="list-style-type: none">• 140 MHz
Aspect Ratio	<ul style="list-style-type: none">• 4:3
Image Size (Diagonal)	<ul style="list-style-type: none">• 1.8 ft. to 20.8 ft. (0.5 m to 6.3 m)
Projection Lens	<ul style="list-style-type: none">• Manual zoom and focus, 1.3:1 zoom ratio• Focal length: 38 mm to 55 mm, f/1.8-2.1
Digital Zoom	<ul style="list-style-type: none">• 16x magnification
Projection Distance	<ul style="list-style-type: none">• 3.6 ft. to 32.8 ft. (1.1 m to 10 m)
Keystone Correction	<ul style="list-style-type: none">• 10
Projection Method	<ul style="list-style-type: none">• front/rear, desktop/ceiling
Lamp (Life)	<ul style="list-style-type: none">• 120 watt UHP (4,000 hours)
Audio	<ul style="list-style-type: none">• 2 x 1 w stereo
Remote Control	<ul style="list-style-type: none">• For projection control
Dimensions	<ul style="list-style-type: none">• 9.5 in. W x 13.6 in. L x 3.9 in. H• 24.2 cm W x 34.7 cm L x 9.9 cm H
Weight	<ul style="list-style-type: none">• 8.1 lbs. (3.7 kg)
Power Consumption	<ul style="list-style-type: none">• 200 watts
Power Requirements	<ul style="list-style-type: none">• 100V-240V at 50/60 Hz (+/- 10%)
Operating Temperature (Sea Level)	<ul style="list-style-type: none">• 41- 95 F (5- 35 C)
On-Screen Menu Languages	<ul style="list-style-type: none">• English, Japanese, German, French, Italian, Spanish
Audible Noise	<ul style="list-style-type: none">• 38db
Approvals	<ul style="list-style-type: none">• FCC Class A, UL, C-UL
Warranty	<ul style="list-style-type: none">• Two years on parts and labor (excluding lamp)